

Rittal – The System.

Faster – better – everywhere.

Digital Brochure

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



Rittal – The System.

Faster – better – everywhere.



Ex Housings

Ex Housings

Stainless steel, empty housing with screw-fastened cover	186
Stainless steel, empty housing with hinged door	187



Ex Housings



System Accessories Page 421

Applications:

- Zone 1 and 2 or 21 and 22 to 94/9/EC
- Ambient temperature range: -22°F...+176°F
- Protection type to EN 60 079: Equipment protection due to increased safety, equipment protection due to housing

Material:

- Housing: Stainless steel 1.4301 (AISI 304)
- Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal

Surface finish:

- Housing: Brushed, grain 240

Protection category IP to IEC 60 529:

- IP 66

Supply includes:

- Housing
- Cover

Certificates:


- PTB 03 ATEX 1013U
- IEC Ex PTB 09.0033U

Approvals:

- ATEX
- IEC

Technical details:

Available on the Internet



Stainless steel, empty housing with screw-fastened cover

Height (H) inches (mm)	Packs of	6 (150)	8 (200)	6 (150)	8 (200)	12 (300)	8 (200)	Page
Width (B) inches (mm)		6 (150)	8 (200)	12 (300)	12 (300)	12 (300)	16 (400)	
Depth (T) inches (mm)		3 (80)	3 (80)	3 (80)	3 (80)	5 (120)	5 (120)	
Model No.	1 pc(s).	9301.000	9303.000	9302.000	9304.000	9306.000	9305.000	
Weight lb (kg)		2.9 (1.3)	4.0 (1.8)	4.0 (1.8)	5.3 (2.4)	8.6 (3.9)	7.9 (3.6)	
Accessories								
Mounting Plates	1 pc(s).	1560.700	1562.700	1561.700	1563.700	1567.700	1564.700	507
Wall Mounting Bracket	4 pc(s).	1594.000	1594.000	1594.000	1594.000	1594.000	1594.000	503
Support Rails TS 35/7.5	10 pc(s).	2314.000	2315.000	2316.000	2316.000	2316.000	2317.000	530
Ground Straps		see page	see page	see page	see page	see page	see page	555



System Accessories Page 421

Applications:

- Zone 1 and 2 or 21 and 22 to 94/9/EC
- Ambient temperature range: -22°F...+176°F
- Protection type to EN 60 079: Equipment protection due to increased safety, equipment protection due to housing

Material:

- Housing: Stainless steel 1.4301 (AISI 304)
- Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal
- Mounting plate: Carbon steel

Surface finish:

- Housing: Brushed, grain 240
- Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

- IP 66

Supply includes:

- Housing
- Door
- Mounting plate

Certificates:


- PTB 02 ATEX 1082U
- IEC Ex PTB 09.0035U

Approvals:

- ATEX
- IEC

Technical details:

Available on the Internet



Stainless steel, empty housing with hinged door

Height (H) inches (mm)	Packs of	12 (300)	15 (380)	12 (300)	15 (380)	24 (600)	24 (600)	30 (760)	30 (760)	39 (1000)	Page
Width (B) inches (mm)		8 (200)	12 (300)	15 (380)	15 (380)	15 (380)	24 (600)	24 (600)	30 (760)	32 (800)	
Depth (T) inches (mm)		6 (155)	8 (210)	6 (155)	8 (210)	8 (210)	8 (210)	8 (210)	12 (300)	12 (300)	
Mounting plate width (F) inches (mm)		6 (162)	13 (334)	13 (334)	13 (334)	13 (334)	22 (549)	22 (549)	28 (704)	29 (739)	
Mounting plate height (G) inches (mm)		11 (275)	11 (275)	11 (275)	14 (355)	22 (570)	22 (570)	29 (730)	29 (730)	38 (955)	
Model No.	1 pc(s).	9401.600	9409.600	9402.600	9403.600	9404.600	9405.600	9406.600	9407.600	9408.600	
Cam lock with 3 mm double-bit insert		1	1	1	1	2	2	2	2	2	
Reinforcement section in the door		-	-	-	-	-	■	■	■	■	
Weight (lb) kg		8.4 (3.8)	17.0 (7.7)	16.3 (7.4)	21.3 (9.7)	29.3 (13.3)	34.3 (15.6)	49.1 (22.3)	67.1 (30.5)	79.9 (36.3)	

Accessories

Wall Mounting Bracket	4 pc(s).	2433.000	2433.000	2433.000	2433.000	2433.000	2433.000	2433.000	2433.000	2433.000	504
Support Rails TS 35/7.5	10 pc(s).	2315.000	2316.000	-	-	-	-	-	-	-	530
Rails for Interior Fitting	4 pc(s).	-	2383.210	-	2383.210	2383.210	2383.210	2383.210	2383.300	2383.300	521
Support Rails TS 35/15	10 pc(s).	-	-	-	-	-	2319.000	2319.000	-	-	530
Ground Straps		see page	see page	see page	see page	see page	see page	see page	see page	see page	555