

Rittal – The System.

Faster – better – everywhere.

Digital Brochure

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

www.rittal.ca



Rittal – The System.

Faster – better – everywhere.



System Accessories

Base/Plinth

Flex-Block Base/Plinth System	424
TS Base/Plinth	426
Base/Plinth	433

Base

Base	435
------------	-----

Walls

Sidewalls	450
Partition Walls	453
Interconnect Kit	458

Baying Systems

Baying	460
--------------	-----

Doors/Locks

Door Models	467
Expansion Accessories for TS Modular Front Design	469
Viewing Windows/Operating Panels	473
Lock Systems	478
Hinges	492
Door, External/Internal	493

Roof/Wall Mounting

Roof	499
Wall Mounting	503

Interior Fittings

Mounting Plates	507
Rail Systems	514
Assembly Components	533
Component Shelves	540
System Lights	545
EMC	551
Interior Fittings for Areas at Risk of Earthquake	554
Grounding	555

Cable Routing

Cable Entry	561
Flange Plates	564
Cable Gland	568
Cable Gland	569
Cable Management	572
Cable Routing 19"	582

19" Installation System

Pivoting Frame	587
Accessories for Data Rack	591
Profile Rails	592
Slide Rails	596
19" Fittings	598
Patch Panels	603
Splicing Boxes	604

Human/Machine Interface

Handles	605
External Mounting Accessories	607
Front Fittings	608
Keyboards, Supports and Drawers	610
Interfaces	617
Signal Pillars	619


Technical Information

RittalXpress	622
CE/Grounding/HD/Model Numbers	623
Protection Categories	624
NEMA	625
Approvals/Equipment Grounding Conductor	627
Coating/Spray Finish	628




Interior Fittings

Component Shelves for Frame Attachment



- 1 Fastening Bolts
- 2 Mounting Rails
- 3 Installation Kit
- 4 Telescopic Rails



Component Shelf for Frame Attachment

Enclosure width 600 and 800 mm for TS and for upgrading existing DK-TS applications

For installation in enclosures without 19" (482.6 mm) fixture.

Max. depth of component shelves = Enclosure depth - 100 mm

Technical specifications:

- Fastening bolts or mounting rails may be installed on a 25 mm hole pattern in the enclosure depth
- Mounting hole for handles provided
- Component shelf, slotted

Material:

- Carbon steel

Color:

- RAL 7035

Supply includes:

- Assembly components

Enclosure width 24" (600 mm)

Load capacity lb (kg) (Surface load, static)	110 (50)	110 (50)	110 (50)	110 (50)	221 (100)	221 (100)	221 (100)
Component shelf height, inches (mm)	1.1 (29)	1.1 (29)	1.1 (29)	1.1 (29)	1.8 (45)	1.8 (45)	1.8 (45)
Component shelf depth, inches (mm)	16 (400)	20 (500)	24 (600)	28 (700)	20 (500)	24 (600)	28 (700)
Model No.	7164.035	7165.035	7166.035	7166.735	7465.035	-	7466.735

Enclosure width 32" (800 mm)

Load capacity lb (kg) (Surface load, static)	110 (50)	110 (50)	110 (50)	110 (50)	221 (100)	221 (100)	221 (100)
Component shelf height, inches (mm)	1.1 (29)	1.1 (29)	1.1 (29)	1.1 (29)	1.8 (45)	1.8 (45)	1.8 (45)
Component shelf depth, inches (mm)	16 (400)	20 (500)	24 (600)	28 (700)	20 (500)	24 (600)	28 (700)
Model No.	7184.035	7185.035	7186.035	7186.735	-	7486.035	7486.735

! Also required:

TS system chassis 17 x 73 mm as installation kit for enclosure depth, inches (mm), see page 522	20 (500)	8612.050	8612.050	8612.050	8612.050	8612.050	8612.050	8612.050
	24 (600)	8612.060	8612.060	8612.060	8612.060	8612.060	8612.060	8612.060
	32 (800)	8612.080	8612.080	8612.080	8612.080	8612.080	8612.080	8612.080
	39 (1000)	8612.000	8612.000	8612.000	8612.000	8612.000	8612.000	8612.000
	47 (1200)	8612.020	8612.020	8612.020	8612.020	8612.020	8612.020	8612.020

+ Accessories:

Telescopic slides, see page 543	7061.000	7081.000	7161.000	7161.700	7065.000	-	7066.700
Handles for component shelves, see page 544	5501.730	5501.730	5501.730	5501.730	5501.730	5501.730	5501.730
Cable support, hinged	see page 544						

Component Shelf, Static Installation

for TS, PC

prepared for fan expansion kit

Mounted directly on the vertical TS enclosure section. Simply locate the 4 pre-installed screws and secure.

Load capacity:

- 40 kg surface load, static

Material:

- Carbon steel

Color:

- RAL 7015

Supply includes:


- Assembly components

For enclosures ¹⁾		Support area		Model No.
Width inches (mm)	Depth inches (mm)	Width inches (mm)	Depth inches (mm)	
24 (600)	24 (600)	20 (507)	22 (550)	8800.900
24 (600)	32 (800)	20 (507)	30 (750)	8800.910

¹⁾ For enclosures without mounting plate

+ Accessories:

- Fan expansion kit 7980.XXX, see page 358



Component shelves for attaching to the 19" system punching

Component Shelf, Static Installation

19" (482.6 mm), depth-variable for TS IT

For static installation between two 19" mounting levels.

- Depth-variable to adapt to individual distances between levels
- Tool-free, time-saving one-person assembly

Material:

- Carbon steel

Surface finish:

- Spray-finished

Color:

- RAL 9005

Supply includes:

- Assembly components

Distance between levels inches (mm)	Load capacity, static lb (kg)	Height U	Packs of	Model No.
16 - 24 (400 - 600)	110 (50)	½	1 set(s)	5501.655
24 - 35 (600 - 900)	110 (50)	½	1 set(s)	5501.665
16 - 24 (400 - 600)	221 (100)	1	1 set(s)	5501.695
24 - 35 (600 - 900)	221 (100)	1	1 set(s)	5501.705



Component Shelf, Pull-Out

19" (482.6 mm) for TS IT

Mounted between two 19" mounting levels.

- Depth-variable to adapt to individual distances between levels
- Tool-free, time-saving one-person assembly from the enclosure front
- Self-locking
- Full withdrawal

Material:

- Carbon steel

Surface finish:

- Spray-finished

Color:

- RAL 9005

Supply includes:

- Component shelf, slotted
- Telescopic slide with mounting kit
- Assembly components

Distance between levels inches (mm)	Load capacity, static lb (kg)	Height U	Depth inches (mm)	Packs of	Model No.
16 - 24 (400 - 600)	110 (50)	1	20 (500)	1 set(s)	5501.675
24 - 35 (600 - 900)	110 (50)	1	28 (700)	1 set(s)	5501.685
16 - 24 (400 - 600)	221 (100)	1½	20 (500)	1 set(s)	5501.715
24 - 35 (600 - 900)	221 (100)	1½	28 (700)	1 set(s)	5501.725



Accessories:

- Handle for component shelf 5501.730, see page 544



Interior Fittings

Component shelves for attaching to the 19" system punching



Component Shelf 2 U, Static Installation

**19" (482.6 mm)
for 19" system punchings**
For mounting on a 19" mounting level.

Load capacity:
– 25 kg surface load, static

Material:
– Carbon steel

Surface finish:
– Spray-finished

Component shelf depth inches (mm)	RAL color	Packs of	Model No.
10 (250)	9005	1 pc(s).	5501.615
16 (400)	9005	1 pc(s).	5501.625

Note:
– Not suitable for combination with telescopic slides

! Also required:

- Captive nuts, see page 538
- Screws, see page 539

Installation Kit, Depth-Variable for 19" component shelves

Depending on the clearance between the two 19" (482.6 mm) levels, the mounting kit is screw-fastened in the depth directly to the 19" (482.6 mm) system punching.

Material:
– Carbon steel

Surface finish:
– Zinc-plated

Supply includes:
– Assembly components

19" clearance between levels inches (mm)	Packs of	Model No.
22 – 33 (550 – 850)	2 pc(s).	7063.850

Installation kits/Accessories for component shelves

TS System Chassis 17 x 73 mm

as installation kit for component shelves

Simply locate and secure. One pack is sufficient for 2 component shelves.

Load capacity:

- 100 kg surface load, static

Material:

- Carbon steel

Surface finish:

- Zinc-plated

Supply includes:

- Assembly components

Installation in enclosure depth inches (mm)	Packs of	Model No.
20 (500)	4 pc(s).	8612.050
24 (600)	4 pc(s).	8612.060
32 (800)	4 pc(s).	8612.080
39 (1000)	4 pc(s).	8612.000
47 (1200)	4 pc(s).	8612.020



Adapter for L Rails

for TS network enclosures

To mount component shelves and slide rails on L rails.

Material:

- Carbon steel

Supply includes:

- Assembly components

Packs of	Model No.
4 pc(s).	7827.300



Telescopic Rails

for component shelves in TS and for upgrading existing DK-TS applications

Fixed component shelves can easily be upgraded to allow full withdrawal. In this case, the existing fastening bolts or mounting rails (heavy-duty version) are replaced with telescopic rails.

Technical description:

- For installation and locking on a 25 mm hole pattern in the enclosure depth

Load capacity:

- 50 kg/100 kg per set

Material:

- Carbon steel

Surface finish:


- Zinc-plated

Load capacity 110 lb (50 kg)

For component shelf depth inches (mm)	Packs of	Model No.
16 (400)	2 pc(s).	7061.000
20 (500)	2 pc(s).	7081.000
24 (600)	2 pc(s).	7161.000
28 (700)	2 pc(s).	7161.700

Load capacity 221 lb (100 kg)

For component shelf depth inches (mm)	Packs of	Model No.
20 (500)	2 pc(s).	7065.000



- 1 Fastening Bolts
- 2 Mounting Rails
- 3 Telescopic Rails

Interior Fittings

Accessories for Component Shelves



Cable Support

hinged, with quick-fit connector

For secure routing of connection cables from the component shelf with telescopic pull-out to the clamping point. Can be released from both sides using the quick-release fastener.

Material:

- Carbon steel

Surface finish:

- Zinc-plated

Supply includes:

- Assembly components

For enclosure depth, inches (mm)	Model No.
< 24 (600)	7163.500
> 24 (600)	7163.550



Cable Support

hinged, with anti-kink device and clamp

For secure routing of connection cables from the component shelf with telescopic pull-out to the clamping point. Kink-free cable routing in the desk unit using mobile chain links. Can be released from both sides using the quick-release fastener.

Material:

- Carbon steel, zinc-plated
- Center section: Plastic

Supply includes:

- Assembly components

For enclosure depth, inches (mm)	Model No.
< 24 (600)	7163.560
> 24 (600)	7163.565



Handles

for pull-out component shelves

The component shelves are designed to allow installations where a handle is required in the application.

Material:

- Die-cast zinc

Surface finish:

- Spray-finished, silver-gray

Supply includes:

- Assembly components

Packs of	Model No.
2 pc(s).	5501.730



Fastening Bolts

for slotted component shelves

Provides non-slip attachment of your components. The bolts are screwed into the slots in the component shelf support surface. This makes them adjustable and suitable for use with any components.

Packs of	Model No.
4 pc(s).	7115.000