

Rittal – The System.

Faster – better – everywhere.

Digital Brochure

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



Rittal – The System.

Faster – better – everywhere.



System Accessories

Base/Plinth

Flex-Block Base/Plinth System	424
TS Base/Plinth	426
Base/Plinth	433

Base

Base	435
------------	-----

Walls

Sidewalls	450
Partition Walls	453
Interconnect Kit	458

Baying Systems

Baying	460
--------------	-----

Doors/Locks

Door Models	467
Expansion Accessories for TS Modular Front Design	469
Viewing Windows/Operating Panels	473
Lock Systems	478
Hinges	492
Door, External/Internal	493

Roof/Wall Mounting

Roof	499
Wall Mounting	503

Interior Fittings

Mounting Plates	507
Rail Systems	514
Assembly Components	533
Component Shelves	540
System Lights	545
EMC	551
Interior Fittings for Areas at Risk of Earthquake	554
Grounding	555

Cable Routing

Cable Entry	561
Flange Plates	564
Cable Gland	568
Cable Gland	569
Cable Management	572
Cable Routing 19"	582

19" Installation System

Pivoting Frame	587
Accessories for Data Rack	591
Profile Rails	592
Slide Rails	596
19" Fittings	598
Patch Panels	603
Splicing Boxes	604

Human/Machine Interface


Handles	605
External Mounting Accessories	607
Front Fittings	608
Keyboards, Supports and Drawers	610
Interfaces	617
Signal Pillars	619

Technical Information

RittalXpress	622
CE/Grounding/HD/Model Numbers	623
Protection Categories	624
NEMA	625
Approvals/Equipment Grounding Conductor	627
Coating/Spray Finish	628



Front fittings



Front panels for Comfort Panel

Material:
– Aluminum, 3 mm

Surface finish:
– Natural anodized

Note:
– Mounting kits included in the supply of 520 mm wide standard housings.

With mounting hole

Height inches (mm)	Width inches (mm)	U	Model No.
6 (155.0)	19 (482.6)	3.5	6027.000
12 (310.3)	19 (482.6)	7	6028.000

With threaded bolts M5

Height inches (mm)	Width inches (mm)	U	Model No.
6 (155.0)	19 (482.6)	3.5	6027.010
12 (310.3)	19 (482.6)	7	6028.010
14 (355.6)	18 (457.2)	–	8015.416
16 (400)	20 (520)	–	6028.014
20 (500)	20 (520)	–	6028.015
24 (600)	20 (520)	–	6028.016



Also required:

– Mounting kit for Comfort Panel 6053.800, see page 609



Cover plate

for support arm connection

To securely lock an unused support arm connection in the housing.

Material:
– Carbon steel

Supply includes:
– Seal and assembly components

Note:
– For Comfort Panels where (2) support arm cut-outs are provided, a cover plate is included in the supply of the housing.

Support arm connection	Surface finish	Model No.
□ 90 x 71 mm	Spray-finished RAL 7024	6505.200
∅ 130 mm	Zinc-plated, clear-chromated	6505.500
□ 120 x 65 mm	Zinc-plated, clear-chromated	6505.100

Mounting kit

for Comfort Panel

For the installation of aluminum front panels, command panels and keyboards.

Supply includes:

- 6058.800, 6053.800:
20 each of retaining claws, captive nuts, screws, nuts and sealing washers
- 6053.300:
8 medium retaining claws, 8 short retaining claws, 4 long retaining claws

1 6058.800, 6053.800

2 6053.300

For drilled holes/bolts/front panel mounting from behind

Thread	Model No.
M4	6058.800
M5	6053.800

For screw clamp

For the installation of	Model No.
Siemens Sinumerik: OP 010, OP 010 C, OP 012, OP 015, OP 015 A, OP 019, MCP 483 C, MCP 483, PP 012, PP 012 extension, MCP, KB 483 C, Qwerty 19"	6053.300
Siemens Simatic: TP 900 Comfort, KP 900 Comfort, TP 1200 Comfort, KP 1200 Comfort, KTP 1000 Basic, KTP 1500 Basic	
Panel PC 477C, 577C, 677C: 12.1"-Key, 12.1"-Touch, 15.1"-Key, 15.1"-Touch, 19"-Touch, 22"-Touch ¹⁾	
MP 377 12"-Touch, MP 377 15"-Touch, MP 377 19"-Touch	
Industrial Flat Panel: IFP 1200 Touch, IFP 1500 Touch, IFP 1200 Key, IFP 1500 Key, IFP 1900 Touch, IFP 2200 Touch	
Industrial Thin Client: ITC 1200, ITC 1500, ITC 1900, ITC 2200	
B & R: Automation Panel, Panel PC	

¹⁾ 2 packs are required

